

SANITARY LIFTS

Mepaco® lifts are ergonomically designed and engineered to minimize lost-time injuries. Designed to USDA specifications, these lifts allow for clean-in-place processes. The EZL2500 and EZ4000 are stock units and are available for quick delivery. Portable and rotary top units are available.



EZL2500 shown in raised position

MODEL EZL2500

- Heavy-Duty T304 SS Construction
- Working Capacity: 2,500 Lbs (1,136 Kg)
- Platform Size: 48" (122 cm) x 44" (112 cm)
- Raised Platform Height: 37 1/2" (95 cm) [42" (107 cm) w/Side Rails]
- Beveled Low-Profile Platform
- Relief Valve to Prevent Overloading
- Controlled Descent in Case of Electrical Failure
- Self-Contained Power Unit
- 115 Volt Single Phase Hydraulic Drive w/Power Unit (Remotely Mounted)
- Safety Up-Down Foot Pedal Control
- Narrow 2.5" (6.4 cm) wide sides for easy loading/unloading
- Totally Enclosed Dual (Synchronized) Hydraulic Lift Cylinders
- Pickle Passivated Finish
- USDA Approved Design



EZL4000 shown with rotary top option

MODEL EZ4000

- Heavy-Duty T304 SS Construction
- Working Capacity: 4,000 Lbs (1,818 Kg)
- Platform Size: 48" (122 cm) x 42" (107 cm)
- Raised Platform Height: 37" (94 cm) [Lowered to 9" (23cm)]
- Relief Valve to Prevent Overloading
- Controlled Descent in Case of Electrical Failure
- Self-Contained Power Unit
- 115 Volt Single Phase Hydraulic Drive w/Power Unit (Integrally Mounted)
- Safety Up-Down Pendant Control
- Dual, Low Pressure Hydraulic Cylinders (White Epoxy)
- Pickle Passivated Finish
- USDA Approved Design

SANITREAD™

SaniTread™ is all 304 stainless decking designed to eliminate food processing deposits and residue. It is suited for work platforms, walkways or stairs and can be welded, bolted or just set in place.

Evenly spaced holes are punched in 12 gauge stainless steel and raised above the surface to provide food traction in all directions. Drain holes are punched between raised holes, providing optimum safety and clean-ability.

